

Blackline F15

Wide-bandwidth system

features

- ▶ Wide-bandwidth system
- ▶ Multi-angle birch ply enclosure
- ▶ User rotatable 80° x 50° horn
- ▶ Top hat fitting for tripod mounting
- ▶ 1.4" (35mm) compression driver
- ▶ Five year limited warranty

applications

- ▶ Live club performance
- ▶ High powered stage monitoring
- ▶ Club installs





portable club

The high power Blackline F15 is a high performance, wide-bandwidth system in an incredibly compact and efficient package. Extended frequency response is provided by a 15" (380mm) LF driver teamed with a 1.4" (35mm) exit compression driver mounted on a rotatable 80° x 50° constant directivity HF horn. The F15 is perfect for higher power applications where ease of installation or speed of deployment are important factors.

technical specifications

| | |
|------------------------|--|
| TYPE | Compact, two-way passive, multi-angled, vented |
| FREQUENCY RESPONSE (1) | 55Hz-18kHz ± 3dB |
| DRIVERS | 15" (380mm) bass driver 1.4" (35mm) exit compression driver |
| RATED POWER (2) | 400W AES, 1600W peak |
| RECOMMENDED AMPLIFIER | 400-800W into 4 ohms |
| SENSITIVITY (3) | 99dB |
| MAXIMUM SPL (4) | 123dB continuous, 129dB peak |
| IMPEDANCE | 8 ohms nominal |
| DISPERSION (-6dB) | 80° horizontal, 50° vertical |
| CROSSOVER | 1.2kHz passive |
| ENCLOSURE | 68 litre, multi-laminate birch ply |
| FINISH | Textured black paint |
| PROTECTIVE GRILLE | Black perforated steel |
| CONNECTORS | 2 x Neutrik NL4 |
| FITTINGS | 12 x M8 inserts Top hat fitting |
| DIMENSIONS | (W) 471mm x (H) 690mm x (D) 443mm (W) 18.5ins x (H) 27.2ins x (D) 17.5ins |
| WEIGHT | 32.5kg (71.5lbs) |

overall dimensions



F15

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2003 Martin Audio Ltd.



www.martin-audio.com